





TYPE 51/TYPE 5

TRAVELLING HEAD GRINDING MACHINES









FLAT GRINDING OF INDUSTRIAL KNIVES

- Programmes for pendulum grinding with roughing-finishing-sparking out
- Rapid change of the grinding segments and work pieces
- Error message in plain text for quick troubleshooting
- Easy programming via parameter input

COMPACT & ROBUST CONSTRUCTION DUE TO HIGH QUALITY COMPONENTS





HIGHLIGHTS TYPE 51/TYPE 5

- Program for deep grinding
- Technology data management:20 memory spaces for:
 - Pendulum grinding
 - Deep grinding
- Electronic power measurement of the grinding motor:
 - Automatic sparking out
 - Power control

- Capacitive hardened glass Touchpanel
- Touchpanel mounted on grinding carriage
- Electronic demagnetizing device
- Direction of rotation reversal of the grinding motor
- Complete guideway cover


- Additional aggregates:
 - electr. central lubrication unit
 - Coolant device
 - Magnetic roller coolant cleaner
 - Grinding dust exhausting unit
 - Paper band filter
 - Manual / Automatic
 - Separate scavenging pump
- Switch cabinet air conditioning



Modern and easy control by means of an innovative Touchpanel



Our manual operating unit guarantees overview and control during the complete grinding process



The robust S1 grinding motor stands for maximum efficiency during machining.

TECHNICAL DATA						
TYPE 51						
Grinding Length [mm]	1000	2100	3100			
Motor [kW]	7.5	11				
Magnetic chuck width [mm]		150 – swiveling				

TYPE 5								
Grinding Length [mm]*	1000	1500	2100	2500	3100	3600	4100	
Motor [kW]	7.5**	11**	13.5***					
Magnetic chuck width [mm]	150 – swiveling		2×100 – swiveling			200 – stationary		

^{*} Other lengths upon request

GET IN TOUCH WITH US TODAY

TOGETHER WE WILL FIND A SOLUTION FOR YOUR REQUIREMENTS

REFORM GRINDING TECHNOLOGY GMBH

Phone: +49 661 4959 00 info@reform.de www.reform.de

01-2020

WE RESERVE THE RIGHT FOR TECHNICAL CHANGES!

^{**} A S1 operation guarantees a permanent, undiminished grinding performance – without break. This standard cannot be offered by our competition in a similar form.

^{***} S6 operation